

COPY OF PAPERS
ORIGINALLY FILED

Please amend claims 14, 21, 24 and 25.

a1
Ech

14. (Amended) A nestable pallet comprising:
a deck member having an upper surface, and a plurality of integrally formed peripheral foot portions extending downwardly therefrom and disposed about the periphery of the deck member, wherein each of the peripheral foot portions has an outwardly directed recess extending to the upper surface of the deck member for receiving a corresponding foot portion of a like pallet disposed thereabove when in a nested orientation.

a2

21. (Amended) The nestable pallet of claim 19, wherein the non-peripheral foot portion has an inner surface and at least one upright member projecting upwardly therefrom.

a3

24. (Amended) A nestable pallet comprising:
a deck member having an upper surface and including a plurality of downwardly extending support members extending therefrom, the support members defining a U-shaped cross-section taken along a plane parallel to the upper surface, the support members further defining correspondingly shaped pockets for nestably receiving the support members of a similar pallet disposed thereabove.

25. (Amended) A nestable pallet comprising:
a top deck having an upper surface and a periphery, and at least one foot member extending from the periphery of the top deck, the at least one foot member having a cutout formed in its exterior surface extending to the upper surface of the top deck, wherein the cutout is arranged to receive a corresponding foot member of another pallet positioned thereabove in a nested orientation.

**COPY OF PAPERS
ORIGINALLY FILED**

Please add new claims 34-39.

Copy
34. (New) The nestable pallet of claim 14, wherein the outwardly directed recess of the foot portion defines a corresponding inwardly directed projection, the recess receiving a corresponding projection of the like pallet disposed thereabove when in the nested orientation.

24
35. (New) The nestable pallet of claim 14, wherein the foot portions have a single-wall construction.

36. (New) The nestable pallet of claim 25, wherein the cutout of the foot member defines a corresponding inwardly directed projection, the cutout receiving a corresponding projection of the another pallet positioned thereabove when in the nested orientation.

37. (New) The nestable pallet of claim 25, wherein the foot member has a single-wall construction.

38. (New) A nestable pallet comprising:
a top deck having an upper surface and a peripheral edge, and at least one foot member extending downwardly from the peripheral edge of the top deck, the at least one foot member having an exterior surface and an interior surface, the exterior surface having a cutout formed therein, the cutout extending vertically to the upper surface of the top deck, the cutout defining a projection on the interior surface of the foot member, wherein the cutout is arranged to receive a corresponding projection of an other pallet positioned thereabove when in a nested orientation.

39. (New) The nestable pallet of claim 38, wherein the foot member has a single-wall construction.